



Kroon-Oil Product recommendation

Isuzu - Trooper 3.1 TD (1992-1998)

Recommended product	ENGINE, 4JG2
	System capacity: 6 liter
Good alternatives	<u>Helar 0W40</u> Usage: Normal, change every 7500 km / 12 months
	<u>Emperol 5W40</u> Usage: Normal, change every 7500 km / 12 months
	<u>Asyntho 5W30</u> Usage: Normal, change every 7500 km / 12 months
Recommended product	DIFFERENTIAL, REAR
	System capacity: 1,8 liter
Good alternatives	<u>Gearlube GL-5 80W90</u> Usage: Normal, check every 15000 km / 12 months
	<u>Unigear HS GL-2/GL-5 80W90</u> Usage: Normal, check every 15000 km / 12 months
	Usage: Normal, change every 45000 km / 36 months
Recommended product	DIFFERENTIAL, REAR, LIMITED SLIP
	<u>Gearlube GL-5 80W90</u> Usage: Normal, check every 30000 km / 24 months
Recommended product	DIFFERENTIAL, FRONT, (4X4)
	System capacity: 1,5 liter
Good alternatives	<u>Gearlube GL-5 80W90</u> Usage: Normal, check every 15000 km / 12 months
	<u>Unigear HS GL-2/GL-5 80W90</u> Usage: Normal, check every 15000 km / 12 months
	Usage: Normal, change every 45000 km / 36 months
Recommended product	TRANSMISSION, MANUAL, MUA5CT 5/1
	System capacity: 2,95 liter
	<u>Asyntho 5W30</u> Usage: Normal, check every 15000 km / 12 months
	Usage: Normal, change every 45000 km / 36 months
Recommended product	TRANSFERBOX
	System capacity: 1,45 liter
	<u>Asyntho 5W30</u> Usage: Normal, check every 15000 km / 12 months
	Usage: Normal, change every 45000 km / 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.



Recommended product

Good alternatives

HYDRAULIC BRAKE SYSTEM

Drauliquid-LV Super DOT 4

Usage: Normal, change every 24 months

Drauliquid-S DOT 4

Usage: Normal, change every 24 months

Recommended product

Good alternatives

HYDRAULIC CLUTCH SYSTEM

Drauliquid-LV Super DOT 4

Usage: Normal, change every 24 months

Drauliquid-S DOT 4

Usage: Normal, change every 24 months

Recommended product

POWER STEERING

ATF Dexron II-D

Usage: Normal, check every 30000 km / 24 months

Recommended product

Good alternatives

GREASE POINTS/NIPPLES

Labora Grease

Usage: Normal, change every 12 months

Lithep Grease 2

Usage: Normal, change every 12 months

Recommended product

COOLING SYSTEM

System capacity: 8,6 liter

Coolant SP 11

Usage: Normal

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.