



Kroon-Oil Product recommendation

Opel - Monterey 3.1 TD (1992-1998)

ENGINE, 4JG2

RemarksSAE 10W and SAE 5W-30 oils are not recommended for sustained high speed driving.

System capacity: 6 liter

Recommended product

Helar 0W40

Usage: Normal, change every 7500 km / 12 months

Good alternatives

Emperol 5W40

Usage: Normal, change every 7500 km / 12 months

Asyntho 5W30

Usage: Normal, change every 7500 km / 12 months

DIFFERENTIAL, REAR

System capacity: 1,8 liter

Recommended product

Gearlube GL-5 80W90

Usage: Normal, check every 15000 km / 12 months

Good alternatives

Usage: Normal, change every 45000 km / 36 months

Unigear HS GL-2/GL-5 80W90

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 45000 km / 36 months

DIFFERENTIAL, REAR, LIMITED SLIP

Recommended product

Gearlube GL-5 80W90

Usage: Normal, check every 30000 km / 24 months

DIFFERENTIAL, FRONT, (4X4)

System capacity: 1,5 liter

Recommended product

Gearlube GL-5 80W90

Usage: Normal, check every 15000 km / 12 months

Good alternatives

Usage: Normal, change every 45000 km / 36 months

Unigear HS GL-2/GL-5 80W90

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 45000 km / 36 months

TRANSMISSION, MANUAL, MUA5CT 5/1

System capacity: 2,95 liter

Recommended product

Asyntho 5W30

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 45000 km / 36 months

TRANSFERBOX

System capacity: 1,45 liter

Recommended product

Asyntho 5W30

Usage: Normal, check every 15000 km / 12 months

Usage: Normal, change every 45000 km / 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.



Recommended product

Good alternatives

HYDRAULIC BRAKE SYSTEM

Drauliquid-LV Super DOT 4

Usage: Normal, change every 24 months

Drauliquid-S DOT 4

Usage: Normal, change every 24 months

Recommended product

Good alternatives

HYDRAULIC CLUTCH SYSTEM

Drauliquid-LV Super DOT 4

Usage: Normal, check every 15000 km / 12 months

Drauliquid-S DOT 4

Usage: Normal, check every 15000 km / 12 months

Recommended product

POWER STEERING

ATF Dexron II-D

Usage: Normal, check every 30000 km / 24 months

Recommended product

Good alternatives

GREASE POINTS/NIPPLES

Labora Grease

Usage: Normal, change every 12 months

Lithep Grease 2

Usage: Normal, change every 12 months

Recommended product

COOLING SYSTEM

System capacity: 8,6 liter

Coolant SP 11

Usage: Normal

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. This sheet refers to an MSDS, which is a part of the Product Information System.