

COOLING SYSTEM SPECIFICATIONS

1986 Isuzu Trooper II

1986 ENGINE COOLING
Isuzu Cooling System Specifications

I-Mark (FWD), Impulse, PUP & Trooper II

COOLING SYSTEM SPECIFICATIONS

RADIATOR CAP

Radiator cap pressure relief valve opens at approximately 13-17 psi (.9-1.19 kg/cm²).

THERMOSTAT

On I-Mark models, thermostat begins opening at 177-182 °F (80.5-83.5°C), and fully opens at 203 °F (95°C). On all other models, thermostat begins opening at 180 °F (82°C), and fully opens at 203 °F (95°C).

COOLANT CAPACITY TABLE

Application	Quarts (L)
I-Mark	6.8 (6.4)
Impulse	
Non-Turbo	
Auto. Trans.	9.2 (8.7)
Man. Trans.	9.3 (8.8)
Turbo	
Auto. Trans.	9.4 (8.9)
Man. Trans.	9.5 (9.0)
Pickup	
Diesel	
Auto. Trans.	11.2 (10.6)
Man. Trans.	9.5 (9.0)
Gas	
Auto. Trans.	7.8 (7.4)
Man. Trans.	8.5 (8.0)
Trooper II	8.5 (8.0)